

NOTES:

Housing: Thermoplastics,UL94V-0

Contact: Copper Alloy

Shell: Copper Alloy/Steel

Voltage Current Rating:1.5 AMP. 30V AC

Insulation Resistance:1000M Ω Min.Contact Resistance:30 M Ω Max.

Dielectric Withstanding Voltage:500W AC

Temperature Range:-35°C to +85°C

Insulator color: Black/White

Plastic material:PBT/LCP/Others

Shell finish:Nickel plated/Tin-Lead plated

Mechanical:

Mating Force:3.5KG MAX

Unmating Force:1.02 KG MIN.

Contact finish:


01: Selective Gold Flash

02: Selective Gold 3U"

03: Selective Gold 5U"

04: Selective Gold 15U"

05: Selective Gold 30U"



东莞市溪榜电子有限公司

DONG GUAN XIBANG ELECTRONICS CO., LTD.

TOLERANCE: X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 X.° ±10° .X.° ±8° .X ±5°	DRAWN BY :	DATE : 2015.08.18	PART NAME: 11.0短体沉板 直边贴板1.1	
			PART NO.	SEE TABLE
	CHECKED BY :	DATE : 2015.08.18	MOLD NO.	
	APPROVED BY :	DATE :	DRAW NO:	2015.08.18
UNIT: mm [inch]			SHEET NO.	1 OF 1
SCALE:1:1 SIZE: A4				