



材料:
 A底座:LCP/PPA (白色)
 B卡件:磷铜 (镀银)
 C簧片: 不锈钢 (镀银)
 D内薄膜: 进口聚酰亚胺(黄色)
 E桃心: 进口尼龙 (灰色)
 F 盖板: 不锈钢301 (清洗)
 G外薄膜: 进口聚酰亚胺(黄色)

主要技术规格:
 1. 额定值: 50mA DC12V
 2. 接触电阻: 50mΩ
 3. 操作力: 250gf±50gf
 4. 行程: 0.25±0.1mm
 5. 绝缘电阻: 100MΩ
 6. 抗电强度: 250V 50HZ 1Min.
 7. 寿命: 5万Cycles

DONG GUAN XI BANG ELECTRONIC CO., LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		SWITCH		DRAWING		Y,C,ZHANG		DWG.No.		SBICL	
PART NO.				CHECK		G.C.Chen		REV.		A1	
UNIT : mm	TOLERANCE OTHERWISE	UP TO 5	±0.2	ANGLE	APPROVAL	DATE					
		ABOVE 5~30	±0.3								
		ABOVE 30	±0.5	σ±3°	SCALE	2:1		PAGE		1 OF 1	
		ANGLE	±.7								