



材料:

- A底座:LCP/PPA (白色)
- B卡件:磷铜 (镀银)
- C簧片: 不锈钢 (镀银)
- D内薄膜: 进口聚酰亚胺黄色)
- E桃心: 进口尼龙 (灰色)
- F盖板: 不锈钢301 (清洗)
- G外薄膜: 进口聚酰亚胺黄色)

主要技术规格:

1. 额定值: 50mA DC12V
2. 接触电阻: 50mΩ
3. 操作力: 250gf±50gf
4. 行程: 0.25±0.1mm
5. 绝缘电阻: 100MΩ
6. 抗电强度: 250V 50HZ 1Min.
7. 寿命: 5万Cycles

DONG GUAN XI BANG ELECTRONIC CO., LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		SWITCH			DRAWING	Y.C,ZHANG	DWG.No.	SBICL
PART NO.					CHECK	G.C.Chen	REV.	A1
UNIT : mm	TOLERANCE OTHERWISE	UP TO 5	±0.2	ANGLE	APPROVAL		DATE	
		ABOVE 5~30	±0.3					
		ABOVE 30	±0.5	0°±3'	SCALE	2:1	PAGE	1 OF 1