



材料:

- A按钮: LCP(黑色)
- B底座: LCP(黑色)
- C盖子: 磷铜H62(镀银)
- D嵌件: 进口磷青铜(镀银与银白色)
- E嵌件: 不锈钢304(银白色)

主要技术规格:

1. 额定值: 10mA DC12V
2. 接触电阻: $\leq 200\text{m}\Omega$
3. 操作力: $100\text{gf} \pm 50\text{gf}$
4. 行程: $0.45 \pm 0.15\text{mm}$
5. 绝缘电阻: $\geq 100\text{M}\Omega$
6. 耐压强度: AC100V 50Hz/1Min.
7. 寿命: 5万Cycles Min
8. 温度范围: -10°C TO $+60^\circ\text{C}$

HAOFU ELECTRONCS TECHNOLOGY CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		DETECTION SWITCH		DRAWING		Y,C,ZHANG		DWG.No.		SBICL	
PART NO.		TD-1624SA-01		CHECK		G.C.Chen		REV.		A1	
UNIT : mm	TOLERANCE	UP TO 5	± 0.2	ANGLE	APPROVAL	SCALE	2:1	PAGE	DATE		1 OF 1
	OTHERWISE	ABOVE 5~30	± 0.3						SCALE		
		ABOVE 30	± 0.5	$0^\circ \pm 3'$							