



材料:

- A底座: 进口增强尼龙 (黑色)
- B线路板:
- C端子: 黄铜 (镀银与银白色)
- D接触片: 覆银铜 (单边覆银与银白色)
- E滑块: 进口增强尼龙 (白、黑色)
- F垫片: 不锈钢 (原色)
- G拉簧: 不锈钢 (原色)
- H盖板: 不锈钢 (白色)
- 按钮: 进口增强尼龙 (黑色)

主要技术规格:

1. 额定值: 50mA MAX
2. 接触电阻: $\leq 200 \Omega$
3. 操作力: $100\text{gf} \pm 50\text{gf}$
4. 行程: $2.0 \pm 0.3\text{mm}$
5. 绝缘电阻: $\geq 100\text{M}\Omega$
6. 耐压强度: AC100V 50HZ/ 1Min.
7. 寿命: 5万Cycles Min

DONG GUAN XI BANG ELECTRONIC CO., LTD

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		MULTI FUNCTION SWITCH		DRAWING		Y,C,ZHANG	DWG.No.	SBICL
PART NO.				CHECK		G.C.Chen	REV.	A1
UNIT :	mm	TOLERANCE	UP TO 5	± 0.2	ANGLE	APPROVAL		DATE
		OTHERWISE	ABOVE 5 ~ 30	± 0.3		SCALE	2:1	PAGE
			ABOVE 30	± 0.5	$0^\circ \pm 3'$			
			ANGLE	$\pm 3'$				