






SPECIFICATIONS


1. ELECTRICAL CHARACTERISTICS
 - 1-1.RATING: DC 12V 2A
 - 1-2.CONTACT RESISTANCE: 20m MAX(INITAL)
 - 1-3.DIELECTRIC WITHSTANDING VOLTAGE:
500V AC FOR ONE MINUTE
 - 1-4.INSULATION RESISTANCE: 100M MIN,
MEASURED BY 500V DC
2. LIFE TEST:MECHANICAL LIFE TEST 10,000 CYCLES.



CIRCUIT



P.C.B. LAYOUT



3	HOUSING	LCP	1	BLACK
2	EARTH TERMINAL	C2680	1	Sn PLATED
1	CONTACT TERMINAL	BeCu	3	Au PLATED
NO.	PARTS	MATERIAL	QTY.	FINISHING



东莞市溪榜电子有限公司

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		CONNECTOR				DRAWING	Y,C,ZHANG	DWG.No.	SBICL
PART NO.						CHECK	G.C.Chen	REV.	A1
	UNIT :	TOLERANCE OTHERWISE	UP TO 5	±0.2	ANGLE	APPROVAL		DATE	16-08-2017
	mm		ABOVE 5 ~30	±0.3		ABOVE 30	±0.5	SCALE	2:1
			ANGLE	±3°					