



Code-X	H	Code-X	H
E	6.0	Q	12
F	6.5	R	12.5
G	7.0	S	13.0
H	7.5	T	13.5
I	8.0	U	14.0
J	8.5	V	15.0
K	9.0	W	15.5
L	9.5	X	16
M	10.0	Y	16.5
N	10.5	Z	17
O	11.0	18	18
P	11.5	19	19



SPECIFICATION

Contact Rating: 50mA,12V DC
 Contact Resistance: 100mΩ max
 Insulation Resistance: 100mΩ min.500V DC
 Dielectric Strength: 250V AC/1minute
 Travel: 0.25mm
 Operating Temp: -30℃~+85℃
 Storage Temp: -30℃~+80℃

PAPT NO	TS-FS1212T-X-X
Operating Force	A:100gf B:160gf C:260gf
Height	Code-X

CIRCUIT DIAGRAM

ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	4	Brass (0.30t)	Plating silvering	——
④	Contact	—	1	F.ag/Sus	Natural	——
③	Base	—	1	PA46		——
②	Cover	—	1	PA46		——
①	Keystake	—	1	PA46		——

MARK	DESCRIPTION	REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: TACT SWITCH
ΔX						units: mm	DWN	DATE	VIEW:	PART NO.:
ΔX						tolerance: X.X ±0.2mm	CHKD	DATE	UNIT: mm/in	DWG NO. TS-FS1212T-X-X
ΔX						X.XX ±0.1mm	APPD	DATE	SIZE: A4	
MARK						X.XXX ±0.05mm				
							DONG GUAN XI BANG ELECTRONIC CO., LTD	WEIGHT	SHEET	REVISION
www.alpsr.com www.gdxjdz.com www.xbswitch.com								1.0g	1/1	A0