




SPECIFICATION

Contact Rating: 50mA, 12V DC
 Contact Resistance: 100mΩ max
 Insulation Resistance: 100mΩ min. 500V DC
 Dielectric Strength: 250V AC/1minute
 Travel: 0.20mm
 Operating Temp: -25°C~+70°C
 Storage Temp: -25°C~+70°C



PAPT NO	TS-3025-X-X-X
Operating Force	B:160gf C:260gf C:350gf
Height	H:A:1.5 B:1.6 C:1.7
Fixed column	A:With B:without



⑤	Terminal	—	2	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/Sus	Natural	—
③	Base	—	1	LCP		—
②	Cover	—	1	Spcc	Plating Nickel	—
①	Keystake	—	1	Pa46		—
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK

					units: mm	DSND	DATE	SCALE: N/A	MODEL TYPE: TACT SWITCH		
					tolerance: X.X ±0.2mm	DWN	DATE	VIEW:	PART NO.:		
					X.XX ±0.1mm	CHKD	DATE	UNIT: mm/in	DWG NO		
					X.XXX ±0.05mm	APPD	DATE	SIZE: A4	TS-3025-X-X-		
REVISIONS					UNSPECIFIED TOLERANCES	DONG GUAN XI BANG ELECTRONIC CO., LTD			WEIGHT 1.0g	SHEET 1/1	REVISION A0