


Contact Rating: 50mA, 12V DC
 触点额定值: 50mA, 12V DC
 Contact Resistance: 100mΩ max
 接触电阻: 最大100mΩ
 Insulation Resistance: 100mΩ min. 500V DC
 绝缘电阻: 100mΩ 最小500V DC

Dielectric Strength: 250V AC/1minute
 介电强度: 250V AC/1分钟
 Operating Temp: -25°C ~ +80°C
 工作温度: -25°C ~ +80°C
 Storage Temp: -30°C ~ +80°C
 储存温度: -30°C ~ +80°C
 Life: 100000
 寿命: 100000



CIRCUIT DIAGRAM

PAPT NO	TS-7473-X
Operating Force	B:160gf C:260gf

					units: mm	DSND		DATE		SCALE: N/A	MODEL TYPE: TACT SWITCH		
					tolerance:	DWN		DATE		VIEW:	PART NO.:		
ΔX					X.X ±0.2mm	CHKD		DATE		UNIT: mm/in	DWG NO		
ΔX					X.XX ±0.1mm	APPD		DATE		SIZE: A4	TS-7473-X		
MARK	DESCRIPTION	DATE	REVISED	APPROVED	X.XXX ±0.05mm	UNSPECIFIED TOLERANCES				DONG GUAN XI BANG ELECTRONIC CO., LTD	WEIGHT 1.0g	SHEET 1/1	REVISION A0
www.alpsr.com www.gdxdz.com www.xbswitch.com													