


P. C. B LAYOUT TOP VIEW

- NOTES:
1. CONTACT CURRENT RATING: 10 A;
 2. CONTACT RESISTANCE: 50 mΩ MAX.;
 3. INSULATION RESISTANCE: 100MΩ MIN.;
 4. DIELECTRIC WITHSTANDING: 36 V AC MIN.;
 5. DURABILITY: 5,000 CYCLES MIN.;
 6. CONNECTOR MATING FORCES: 29.4N (3.00Kgf) MAX.;
 7. CONNECTOR UNMATING FORCES: 2.94N(0.30Kgf) MIN.;



	MATERIAL	PLATING
axis support	Brass	silver
plastic	Pbt	
terminal 1	Brass	silver
terminal 2	Phosphor Bronze	silver
terminal 3	Brass	silver

REVISIONS					UNSPECIFIED TOLERANCES		DSND	DATE	SCALE: N/A	MODEL TYPE: DC POWER JACK		
ΔX					ANGLAR	±5°	DWN	DATE	VIEW:	PART NO.:		
ΔX					X.X	±0.2mm	CHKD	DATE	UNIT: mm	DWG NO.:		
ΔX					X.XX	±0.1mm	APPD	DATE	SIZE: A4	DC-042E		
MARK	DESCRIPTION	DATE	REVISED	APPROVED	X.XXX	±0.05mm				WEIGHT	SHEET	REVISION
										1.0g	1/1	A0

www.switchsmt.com

东莞市溪榜电子有限公司