



Ordering information:

PJ-201M-C □□ 0A T □□ 4  
(1) (2) (3) (4) (5) (6) (7)

(1): Series No

(2): Schematic option: C

(3): Material of housing:

AB=ABS

PB=PBT(Standard)

(4): Housing color:

0A=Black (Standard)

Zero-2=Red

3=Orange

4=Yellow

(5): Terminal plating

6=Blue(Sn)(Standard)

8=Silver(Ag)

(6): Special option

0N=Bushing is Nickel plating

(Standard)

0G=Bushing is Gold plating

(7) 0C=Bushing is Cu&Tin Plating

4=Bag packing

SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance: < 30mΩ;
3. Insulation resistance: > 100MΩ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-25N;
6. life test: 5,000 cycles.

					DSND		DATE		SCALE: N/A	MODEL TYPE: 2.5 PHONE JACK		
					ANGLAR	±5°	DWN		VIEW:	PART NO.:		
Δ X					X.X	±0.2mm	CHKD		UNIT: mm	DWG NO.:		
Δ X					X.XX	±0.1mm	APPD		SIZE: A4			
Δ X					X.XXX	±0.05mm						
MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES					WEIGHT	SHEET	REVISION
REVISIONS										1.0g	1/1	A0