


Recommended PCB Layout
Top View

Model No.	PJ-242A-SMT	PJ-242B-SMT	PJ-242C-SMT	PJ-242D-SMT
Schematic				
PIN				
1	sleeve	sleeve	sleeve	sleeve
2	tip	tip	tip	tip
3	ring 1	ring 1	ring 1	ring 1
4	ring 2	ring 2	ring 2	ring 2
10	NP	tip switch	NP	tip switch
11	NP	NP	ring 1 switch	ring 1 switch



	MATERIAL	PLATING
terminal 1	Phosphor Bronze	Gold
terminal 2	Phosphor Bronze	Gold
terminal 3	Phosphor Bronze	Gold
terminal 4	Phosphor Bronze	Gold
terminal 10	Phosphor Bronze	Gold
terminal 11	Phosphor Bronze	Gold
plastic	High Temp. Thermoplastic	

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: 2.5 PHONE JACK
△ X					ANGLAR ±5°	DWN	DATE <td>VIEW: </td> <td>PART NO.:</td>	VIEW:	PART NO.:
△ X					X.X ±0.2mm	CHKD	DATE <td>UNIT: mm</td> <td>DWG NO.:</td>	UNIT: mm	DWG NO.:
△ X					X.XX ±0.1mm	APPD	DATE <td>SIZE: A4</td> <td></td>	SIZE: A4	
					X.XXX ±0.05mm				WEIGHT 1.0g
									SHEET 1/1
									REVISION A0