





DET "A"
2:1

NOTES:

Housing: Thermoplastics,UL94V-0

Contact: Copper Alloy

Shell: Copper Alloy/Steel

Voltage Current Rating:1.5 AMP. 30V AC

Insulation Resistance:1000MΩ Min.

Contact Resistance:30 MΩ Max.

Dielectric Withstanding Voltage:500W AC

Temperature Range:-35℃ to +85℃

Insulator color: Black/White

Plastic material:PBT/LCP/Others

Shell finish:Nickel plated/Tin-Lead plated

Mechanical:

Mating Force:3.5KG MAX

Unmating Force:1.02 KG MIN.

Contact finish:

01: Selective Gold Flash

02: Selective Gold 3U"

03: Selective Gold 5U"

04: Selective Gold 15U"

05: Selective Gold 30U"

东莞市溪榜电子有限公司

DONG GUAN XIBANG ELECTRONICS CO., LTD.

TOLERANCE: X.XX ±0.20 X.XXX ±0.10 X.X ±0.05 X.X ±0.025	DRAWN BY : DATE : 2015.08.18	PART NAME: 沉板破板180度卷边
CHECKED BY : DATE : 2015.08.18	APPROVED BY : DATE : 2015.08.18	PART NO. : MOLD NO. : DRAW NO. : SHEET NO. : 1 OF 1
UNIT: mm [inch] SCALE: 1:1 SIZE: A4		