



GUIDANCE PLATE	1PCS	PA6	Black	————
Contact	1PCS	Ag	————	————
Shrapnel	1PCS	Beryllium Copper	————	————
Knove	1PCS	PA66	Gray	————
Cover	1PCS	PA66	Black	————
Base	1PCS	PA66	Black	————
Terminal	3PCS	Brass	Ag Plated	————

1. 额定电压	DC 30V	7. 自由位置 (FP)	9. 80 ± 0.80mm
2. 额定电流	1A	8. 动作位置 (OP)	8. 60 ± 0.80mm
3. 绝缘电阻 (IR)	50兆欧 (Min)	9. 行程 (PT)	1.20 ± 0.8mm
4. 接触电阻 (CR)	100毫欧 (Max)	10. 机械寿命	20,000次
5. 操作力 (OF)	30 ± 10gf	11. 电气寿命	20,000次
6. 回弹力 (RF)	————	12. 耐压 (WV)	AC250V 1分钟

东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

TOLERANCE: X.XX ±0.30 X.XXX ±0.20 X.XXX ±0.10 X.X ±0.10 X.X ±0.05	DRAWN BY :	DATE : 2015.08.18	PART NAME:	
 UNIT: mm [inch] SCALE: 1:1 SIZE: A4	CHECKED BY :	DATE : 2015.08.18	PART NO.	————
	APPROVED BY :	DATE : 2015.08.18	MOLD NO.	————
			DRAW NO.	————
			SHEET NO.	1 OF 1