







SCHEMATIC

SCHEMATIC (NON-SHORTING)



下压行程	电路说明
0~0.5mm	1与2通, 5与6通; 2与3断, 4与5断。
0.5~0.9mm	电路转换位置
0.9~2.6mm	1与2断, 5与6断; 2与3通, 4与5通。

SPECIFICATIONS

- (1)LIFE TEST:10000cycles at a speed of 15-18cycles
- (2)CONTACT RESISTANCE:100mΩmax
- (3)INSULATION RESISTANCE:100MΩmin
- (4)DIELETRIC STRENGTH:250V AC FOR 1MIN
- (5)OPERATING TEMPERATURE:-16°C-+60°C
- (6)RATING: 0.1A 30V DC
- (7)FUNCTION:2P2T
- (8)TIMING:NON-SHORTING
- (9)OPERATING FORCE:180gf±50gf

NO.	PARTS	MATERIALS	Q'TY		TOLERANCE UNLESS SPECIFIED				
8									
7									
6					WITHIN 1.5mm : ±0.1mm	A	2016-10-14	初版	
5	SPRING	SUS304	1	NATURAL	OVER 1.5mm : ±0.2mm	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.
4	CAM STICK	SUS304	1	NATURAL	TITLE : VERTICAL PUSH SWITCH				
3	CASE	PA66/BRASS STRIP	1	GREY/Ag PLATED	MODEL:				
2	COVER	PA66+15%F.G	1	BLACK	UNIT : mm				
1	NOB	PA66+15%F.G/PBS STRIP	1	BLACK/Ag CLAD	SCALE: 5:1				
					DWN.				
					2016-10-14				
					CHK'D				
					2016-10-14				
					APPD.				



东莞市溪榜电子有限公司